

# SAFETY DATA SHEET CLEENOL HI-SHINE

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name CLEENOL HI-SHINE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Supplier Cleenol Group Ltd

Neville House Beaumont Road

Banbury

Oxon OX16 1RB

UK

Tel: +44 (0)1295 251721 Fax: +44 (0)1295 269561 sales@cleenol.co.uk

#### 1.4. Emergency telephone number

Emergency telephone Emergency contact number (9am to 5pm Monday to Friday excluding bank holidays): 01295

251721 ask for technical, quoting the product name.

Emergency Action: In the event of a medical enquiry involving this product outside of these hours, please contact your doctor or local hospital accident and emergency department or the NHS enquiry service (dial 111) again quoting product name and where applicable present this

MSDS to the medical professional.

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 1 - H224

Health hazards Not Classified

Environmental hazards Not Classified

Classification (67/548/EEC or F+;R12.

1999/45/EC)

## 2.2. Label elements

#### **Pictogram**



Signal word Danger

**Hazard statements** H224 Extremely flammable liquid and vapour.

Revision date: 29/09/2017 Revision: 4 Supersedes date: 05/05/2017

#### **CLEENOL HI-SHINE**

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P501 Dispose of contents/ container to ...

Supplementary precautionary

statements

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

#### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

BUTANE 10-30%

CAS number: 106-97-8 EC number: 203-448-7

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Gas 1 - H220 F+;R12

Press. Gas

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

General information Move affected person to fresh air at once. Get medical attention if any discomfort continues.

**Inhalation** Move affected person to fresh air at once. When breathing is difficult, properly trained

personnel may assist affected person by administering oxygen. Keep affected person warm

and at rest. Get medical attention immediately.

**Ingestion** Not relevant.

**Skin contact** Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

**Eye contact** Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues.

## 4.2. Most important symptoms and effects, both acute and delayed

## 4.3. Indication of any immediate medical attention and special treatment needed

#### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray,

fog or mist.

## 5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

#### 5.3. Advice for firefighters

#### **CLEENOL HI-SHINE**

Protective actions during firefighting

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.2. Environmental precautions

#### 6.3. Methods and material for containment and cleaning up

#### Methods for cleaning up

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. If leakage cannot be stopped, evacuate area.

#### 6.4. Reference to other sections

#### SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Usage precautions

Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

## 7.3. Specific end use(s)

#### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure limits

#### **BUTANE**

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³ Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³ WEL = Workplace Exposure Limit

Ingredient comments

WEL = Workplace Exposure Limits

#### 8.2. Exposure controls

#### Protective equipment





## Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374.

## Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Revision date: 29/09/2017 Revision: 4 Supersedes date: 05/05/2017

#### **CLEENOL HI-SHINE**

Hygiene measures Do not smoke in work area. Wash at the end of each work shift and before eating, smoking

and using the toilet. Promptly remove any clothing that becomes contaminated. When using

do not eat, drink or smoke.

Respiratory protection No specific recommendations. Respiratory protection must be used if the airborne

contamination exceeds the recommended occupational exposure limit.

#### **SECTION 9: Physical and Chemical Properties**

#### 9.1. Information on basic physical and chemical properties

#### 9.2. Other information

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

## 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Strong oxidising agents. Strong alkalis. Strong mineral acids.

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

Hazardous decomposition

products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

## SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Other health effects Carcinogen Category 3.

Inhalation May cause respiratory system irritation. Vapours may cause headache, fatique, dizziness and

nausea. Prolonged inhalation of high concentrations may damage respiratory system.

**Skin contact** Product has a defatting effect on skin. May cause skin irritation/eczema.

**Eye contact** Irritating to eyes.

Route of exposure Inhalation

## SECTION 12: Ecological Information

**Ecotoxicity** Not regarded as dangerous for the environment.

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

12.4. Mobility in soil

## 12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

## SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

## **CLEENOL HI-SHINE**

**Disposal methods** Empty containers must not be punctured or incinerated because of the risk of an explosion.

Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

## **SECTION 14: Transport information**

#### 14.1. UN number

UN No. (ADR/RID) 1950 UN No. (IMDG) 1950 UN No. (ICAO) 1950

#### 14.2. UN proper shipping name

Proper shipping name

**AEROSOLS** 

(ADR/RID)

Proper shipping name (IMDG) AEROSOLS
Proper shipping name (ICAO) AEROSOLS
Proper shipping name (ADN) AEROSOLS

#### 14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID label 3

IMDG class 2.1

ICAO class/division 2.1

ICAO subsidiary risk N/A

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group 5°F IMDG packing group N/A

ICAO packing group N/A

#### 14.5. Environmental hazards

#### 14.6. Special precautions for user

**EmS** 2-13

Emergency Action Code N/A

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

## SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Guidance Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG228.

Approved Classification and Labelling Guide (Sixth edition) L131.

## **CLEENOL HI-SHINE**

## 15.2. Chemical safety assessment

#### SECTION 16: Other information

Revision date 29/09/2017

Revision 4

Supersedes date 05/05/2017

SDS number G10

Risk phrases in full R12 Extremely flammable.

Hazard statements in full H220 Extremely flammable gas.

H224 Extremely flammable liquid and vapour.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.